



PNT High Flow / Aereo is special tire gauge that brings safety, sturdiness, precision and speed needed to calibrate the tires of large vehicles.

The High Flow version was developed for calibrating off-road tires with jumbo nozzles at pressures up to 160 PSI, and with maximized calibration speed.

The Aereo version is ideal for aircraft tires or vehicles that require pressures up to 300 PSI.



Easy operation



Resistant keyboard



Neutral colors, smooth finish, and easy cleaning



Crystal display with internal illumination

PRODUCT FEATURES

Applications:	Vehicles:	Technical Specification:
Airports	PNT High Flow:	Setting Pressure:
Hangars	Tractors	4 a 160 Psi (0,3 - 10 Bars) - PNT High Flow
Farms	Agricultural machineries	4 a 300 Psi (0,3 - 20 Bars) - PNT Aereo
Mining	Road vehicles (off road)	Weight Net/Gross: 7/9 Kg
	*** Does not apply for trucks / buses tire	Dimensions: 39 x 31 x 14 Cm
	PNT Aereo:	Voltage: 110 or 220 Vac
	Airplanes	Max Consumption Power: 20 Watts
		Operating Temperature: 0 to +50°C
		Compatible: Air and Nitrogen

► Additional Information:

- Easy installation;
- Low energy consumption;
- Fast, safe and precise calibration;
- 1 year warranty;
- Audible and visual signals at the end of operation;
- Waterproof and dustproof;
- Converts pressure unit to PSI/BAR, BAR/PSI





PNT 5

PNT 4

PNT JUMBO

PNT PAY AIR

PNT HIGH
FLOW / AEREO

PNG UTG

PNT 5
SELF CONTAINED TOWER



- Precise Information
- Easy Operation and Management
- Alerts and Email Notification
- Meets the Standards

Find out more about the ELS SYSTEM, a complete solution to control the fuel inventory of the gas station

ENERGY SAVING

"Well-calibrated tires reduce fuel consumption and protect the environment, while providing better safety when driving."

CERTIFICATIONS

The EXCELbr Digital Tire Gauges are produced according to national and international technical standards specifications.



Notes: